



Technical Features	Operating Range	Material
<ul style="list-style-type: none"> ▶ Single seal ▶ Multiple springs ▶ Bi-directional ▶ PTFE bellows ▶ Externally mounted ▶ Replaceable seal face 	<ul style="list-style-type: none"> ▶ $d_1 = 25 - 65$ mm ▶ $p = 10$ bar ▶ $t = -40 / 120$ °C ▶ $V_g = 16$ m/sn 	<ul style="list-style-type: none"> ▶ Rotary seal faces: Carbon, Silicon carbide, Tungsten Carbide, Chrome Nickel ▶ Stationary seal faces: Silicon carbide, Ceramic, Tungsten Carbide, Chrome Nickel ▶ Elastomers : Viton (FKM), EPDM, Nitril (NBR)
Stationary Seat Alternatives:		
▶ Standard seats		

Seat alternatives

★ STANDARD SEATS

Dimensions in mm						
d	D	D1	D2	L	L1	L2
25	60	60	47	43.5	11	8.0
25.400	60	60	47	43.5	11	8.0
28.575	67	65	53	43.5	11	8.0
30	67	65	53	43.5	11	8.0
34.925	72	70	57	43.5	11	8.0
35	72	70	57	43.5	11	7.5
40	78	76	62	43.5	11	7.5
45	84	80	70	47.5	11	8.0
50	88	85	72	47.5	11	8.0
55	93	90	77	47.5	11	8.0
60	98	95	82	52.0	11	8.0
65	103	100	87	52.0	11	8.0